



www.blauer-engel.de/uz128

TECHNICAL SPECIFICATON

Construction
 Pile Material
 Backing
 Pile Insert Weight
 Pile Height
 Total Thickness
 Dimensions
 Total Weight
 Comfort Class
 Stress Range
 Colour Fastness to Light
 Colour Fastness to Water
 Flammability
 Thermal Resistance
 Impact Noise Reduction
 Anti-Static Rating
 Vertical Resistance
 Cut Resistance
 Suitable for Office Chairs
 Suitable for Stairs
 Suitable for WW-Floorheating
 Suitable for House Dust allergic Persons
 GUT
 Blauer Engel (Blue Angel)
 Country of Manufacture

INTERLAND Sheet

Loop (ondule)
 80% Goat Hair
 20% Wool
 Jute
 c. 1200 g/m²
 c. 5 mm
 c. 7,2 mm
 c. 200 cm
 c. 2,7 kg / m²
 LC2
 22 (normal)
 5
 4-5
 Cfl-s1 (B1)
 c. 0,12 m² K/W
 c. 22 dB
 - 1,3 kV
 c. 10⁹ Ω
 yes
 yes *1
 yes *2
 yes
 yes

Germany



INTERLAND Tiles

Loop (ondule)
 80% Goat Hair
 20% Wool
 Non-woven
 c. 1200 g/m²
 c. 5 mm
 c. 8,0 mm
 c. 50 x 50 cm
 c. 3,7 kg / m²
 LC2
 22 (normal)
 5
 4-5
 Cfl-s1 (B1)
 c. 0,11 m² K/W
 c. 24 dB
 - 1,3 kV
 c. 10⁹ Ω
 yes
 yes *1
 no
 yes
 yes

Germany



EVER Sheet

(produced without
 mothproofing)
 Loop (ondule)
 80% Goat Hair
 20% Wool
 Jute
 c. 1200 g/m²
 c. 5 mm
 c. 7,2 mm
 c. 200 cm
 c. 2,5 kg / m²
 LC2
 22 (normal)
 5
 4-5
 Cfl-s1 (B1)
 c. 0,11 m² K/W
 c. 23 dB
 - 1,3 kV
 c. 10⁹ Ω
 yes
 yes *1
 yes *2
 yes
 yes

FC7F42F7


www.blauer-engel.de/en/uz128

Germany



*1 with underlays for office chairs

*2 in connection with tretford stair-profiles



Colour variations to samples are possible. 08/2019, subject to modification.