

floors@home/20

floors@home/30

floors@home/40

Covering type according to ISO 10582	Heterogeneous Planks / Tiles, type 1		
Number of colours	28 planks / 7 tiles	77 planks / 27 tiles	21 planks / 4 tiles
Packaging per box/pallet	3.34 m <sup>2</sup> /240.48 m <sup>2</sup> 600x600 mm: 3.24 m <sup>2</sup> /233,28 m <sup>2</sup>		
Performance classification EN ISO 10582 / ISO 10874	22	23, 31	23, 32, 41
Total thickness ISO 24346	2.0 mm		
Wearlayer thickness ISO 24340	0.2 mm	0.3 mm	0.4 mm
Surface treatment	yes/PU		
Bevelled edges	no	yes (depending on design)	
Total weight ISO 23997	3.20 kg/m <sup>2</sup>	3.51 kg/m <sup>2</sup>	3.35 kg/m <sup>2</sup>
Residual indentation ISO 24343-1	≤ 0.1 mm*		
Dimensional stability ISO 23999	≤ 0.15 %*		
Castor chair suitability ISO 4918	yes – using EN 12529, type W		
Underfloor heating EN 1264-2	suitable up to 28°C		
Behaviour to fire EN 13501-1	Bfl-s1		
Resistance to thermal conductivity ISO 8302/ EN 12667	0.02 m <sup>2</sup> K/W		
Electrical propensity when walked upon EN 1815	< 2 kV		
Impact sound improvement ISO 10140-3	2 dB		
Colour fastness to artificial light ISO 105-B02/02	≥ 7		
Electrostatic characteristics EN 1081	> 10 <sup>12</sup>		
Chemical resistance ISO 26987	conforms**		
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)		
Adhesive recommendation	see installation instruction		
Maintenance/Cleaning recommendation	Dr. Schutz		

\* Averaged value

(Date: 01/01/2019)

\*\* Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

